



Orbit

Journal of the Radio Amateur Space Program

No. 18

March/April 1984
\$2.50 U.S.A./Canada



Published by AMSAT — The Radio Amateur Satellite Corporation

Star Performers!

ICOM's VHF/UHF Pairs for Satellite Communications

Oscar 10. Are you ready? Join the future of amateur satellite communications with ICOM VHF and UHF transceivers. Read why ICOM is...*Simply the Best* for satellite communications.

IC-271A, 471A Twins

This new series of VHF/UHF base stations offers a combination of features and flexibility found in no other transceiver anywhere. For receiving MODE J downlink, the IC-471A features a less than 0.5 microvolt for 10dB quieting SSB receiver plus an optional mast-mounted GaAs FET preamplifier with a 15dB gain.

Thirty-two tunable memories keep the IC-471A ready to go on frequency and to monitor the beacon frequencies. A good noise blanker plus all-mode squelch make listening a real pleasure. 40Hz variable speed tuning, which automatically shifts to 100Hz when needed, and a low-noise PLL filter locks to 10Hz makes the frequency resolution of the ICOM twins



ICOM's Stackable Portable Twins IC-290H & IC-490A

second to none. For MODE B use, the IC-471A features a 10W SSB transmitter with variable power control.

The same basic features of the IC-471A apply to the IC-271A and an optional internal preamplifier with front panel switch is available. The IC-271A

transmitter features 25W of transmitter power.

The IC-471A and the IC-271A both have options for computer interfacing. The ICOM BUS is brought out through an optional interface to the back of the radio. From this point, it may be routed to the ICOM computer

interface terminal, mounted in a matching box that will convert the ICOM BUS to RS232C standard. Allowing computer control of both transceiver units, this capability, plus the antenna-tracking programs available for Oscar 10, will make the IC-271A and 471A twins the ultimate for computer control of your satellite operations.

IC-290H/IC-490A Twins

ICOM's IC-290H and IC-490A mount together as a stackable, mountable pair that offers versatility, portability and satellite capability in an amazingly small size. These units are easily hung from your ham shack bench, taken on portable operations or used mobile.

Each features multiple tuning rates, intermodes, FM/SSB/CW, programmable scan and priority function, and an all-mode squelch. The IC-290H has a 25W transmitter, the IC-490A, 10W. Both of these transceivers are high quality designs by ICOM and offer all the flexibility needed for satellite operations.



IC-371A VHF Multi-mode 2 Meter / 25 Watts



IC-471A UHF Multi-mode 430 - 450 MHz / 10 Watts



ICOM

The World System



March/April 1984
Volume 5 Number 2

ORBIT Staff

Editor: Harold Winard, KB2M
Contr. Editor/Staff Liaison:
Vern Riportella, WA2LQQ
Assoc. Editor: Dom Mallozzi, N1DM
Managing Editor: Bob Myers, W1XT
Advertising Dir.: Roger Soderman, KW2U
Illustrations: Norma Adamson

AMSAT Board of Directors

John Browning W6SP (Chairman), Tom
Clark W3IW, John Pronko W6XN, Jan
King W3GEY, Pat Gowen G3IOR, Harry
Yoneda JA1ANG, John Henry VE2VQ

AMSAT Officers

President: Tom Clark, W3IW
Exec. Vice Pres.: V. Riportella, WA2LQQ
Sr. Vice Pres.: J. Champa, K8OCL
V. P., Engineering: Jan King, W3GEY
V. P., Operations: D. Loughmiller, KO5I
V. P. Special Projects: Bill Brown K9LF
Asst. V. P., Eng.: Harold Price, NK6K
Asst. V. P., Eng.: Phil Karn, KA9Q
Asst. V. P., Eng.: S. Robinson, W2FPY
Asst. V. P., Ops. (S/C Ops):
Rick Dittmer, WH6AMX
Asst. V. P., Ops. (User Services):
Ralph Wallio, W0RPK
Treasurer: Jack Colson, W3TMZ
Corporate Secretary: Martha Saragovitz

Headquarters Office Staff

General Manager/Exec. Director:
William Lazzaro, N2CF
Office Manager: Martha Saragovitz

Editorial Office: P.O. Box 575,
Wharton, NJ 07885

Advertising Office: 221 Long Swamp
Road, Wolcott, CT 06716
Phone: 201-666-2870

AMSAT: P.O. Box 27, Wash., DC 20044.
Telephone: 301 589-6062
Telex: 248-566

Second Class postage paid at Waterbury,
Conn. by ORBIT, 221 Long Swamp Road,
Wolcott, Connecticut 06716.

ORBIT (USPS 041-850) is published six
times per year for \$15. (inseparable from
membership dues of \$24).

Copyright © 1984 by AMSAT. Contents
may be reproduced without specific per-
mission provided proper credit is given,
unless otherwise stated and copies are
sent both to AMSAT and to the author.
Opinion expressed is not necessarily that
of AMSAT.

CONTENTS

Technical Features:

- 5 **JAS-1: Japan's First Amateur Radio Satellite
An Innovation Trilogy** PART II
By Shigetake Morimoto, JA1NET; Harry Yoneda, JA1ANG;
Haruo Kanawa, JA1JHF; and JAMSAT
*The first Amateur Radio Satellite from Japan is described
in some detail*
- 7 **A Satellite Builder's Odyssey: January 6 to 18, 1984**
By Harold Price, NK6K
*A sophisticated satellite was built in record time. Here's
just one of the short stories of dedication which made it
all come together.*

Informational Topics:

- 12 **A Survey of OSCAR Station Equipment** PART II
By Harold Winard, KB2M and Roger Soderman, KW2U
*Equipment needed to put together an operational satellite
communications station is described in detail.*
- 11 **Call for Nominations**

Departments:

- 3 **Ellipsis...** By Harold Winard, KB2M
- 21 **AMSAT News**
Minutes of the 1983 Board of Directors Meeting
- 18 **Worldwide Satellite Activity** By Pat Gowen, G3IOR
- 17 **W6 Space Philosopher** By John Browning, W6SP

Our Cover: A circularly polarized log periodic antenna covering 125
MHz to 1 GHz as installed at an ITT antenna test range. The six-foot
long antenna rides on a 65 foot radius arch. Photo taken from the
ground looking skyward. Entire structure including guys is non-
metallic to avoid patten distortions. Range is used to test satellite
communication and general purpose UHF antennas. (Courtesy ITT
and WA2LQQ)

**The BEST is still
"made in U.S.A."**



MIRAGE

**American made RF Amplifiers and Watt/SWR Meters
of exceptional value and performance.**

• 5 year warranty • prompt U.S. service and assistance

RF AMPLIFIERS

2 METERS-ALL MODE

B23 2W in=30W out \$89.95
(useable in: 100 mW-5W)

B108 10W in=80W out \$179.95
(1W=15W, 2W=30W) RX preamp

B1016 10W in=160W out \$279.95
(1W=35W, 2W=90W) RX preamp

B3016 30W in=160W out \$239.95
(useable in: 15-45W) RX preamp
(10W=100W)

220 MHz ALL MODE

C106 10W in=60W out \$199.95
(1W=15W, 2W=30W) RX preamp

C1012 10W in=120W out \$289.95
(2W=45W, 5W=90W) RX preamp

C22 2W in=20W out \$89.95
(useable in: 200mW-5W)

RC-1 AMPLIFIER

REMOTE CONTROL \$24.95
Duplicates all switches, 18' cable

WATT / SWR METERS

- peak or average reading
 - direct SWR reading
- MP-1** (HF) 1.8-30 MHz
MP-2 (VHF) 50-200 MHz
\$119.95

430-450 MHz ALL MODE

D24 2W in=40W out \$199.95
(1W=25W)

D1010 10W in=100W out
(1W=25W, 2W=50W) \$319.95

Available at local dealers throughout the world.

MIRAGE
COMMUNICATIONS EQUIPMENT, INC.

P.O. Box 1393, Gilroy, CA 95020 (408) 847-1857

Ellipsis...

An Editorial by Harold Winard, KB2M

Standards

Perhaps many of us are too close to the action to see it. There's a very important battle going on now within the computer industry. It will have consequences for all of us. Manufacturers, designers, software writers, and users are battling to decide whose computer standard will carry the hearts and pocketbooks of the American public.

Millions are at stake in the computer industry. Advocates on all sides of the issue see the battle as too critical to lose. As the drama unfolds, the hero (or villain, depending on your prejudices) has created a de facto standard in the world of business. IBM has had incredible success in establishing the IBM Personal Computer as the machine of choice for many American businesses. It's starting to become a hot seller overseas as well. Indeed, if an IBM computer is not available, businesses snap up clones, such as the Compaq, Columbia, Corona, or other MS-DOS-compatible machine.

For better or worse, IBM jumped from no share of the market in 1981 to a position of dominance in 1984. By year's end, a PC will be rolling off the assembly line in Boca Raton at the rate of one each seven seconds — all this just three years after the PC was first introduced.

Does this heavy-handed dominance of the computer industry augur well for the computer user? Overall, we think so. Although unanimity on the IBM standard might stifle more creative hardware and software approaches, it does create a solid, sure footing for computer technology. A community that is assured of the long-term integrity of its investment is more apt to invest. What does this have to do with amateur radio and satellites? Our avocation too is seeing exciting times. Silicon chips that fuel the computer revolution also change the way radio amateurs communicate. And it's a very significant change too.

Although cw replaced spark, phone merely supplemented cw. So too has digital communications arrived on our doorstep, not as a replacement for those earlier modes but as a valuable complement. People still enjoy communicating with their voices and that will, we are sure, continue for a long time. And people have also com-

municated with written language, and amateur facsimile and radio teleprinting have been with us for at least 40 years. But the new kid on the block, still in diapers but growing fast, is a form of digital communications called packet radio. It's a robust child, still wet behind the ears, but full of vigor and promise. It's also a confused child, still groping at its future and uncertain of the direction it will take.

Although reminiscent of radio teletypewriter communications, packet is nevertheless very different and offers a wide range of options for error-free communications, high-speed data transfer, store-and-forward techniques, and computer bulletin-board operation. Where teletype (and its newest cousin, AMTOR) are mainly used in a people-to-people mode, packet radio finds its real strength in establishing communications between computers. But in amateur radio, just as in the computer industry, standards will play a key role in deciding what the future holds.

In 1982, an AMSAT-sponsored conference resulted in a very important agreement on basic packet radio protocols. That meeting brought us the AX.25 specification for amateur digital packet communication and set the stage for the current boom in interest in the technique. This standardization came just in time, for the newly founded Tucson Amateur Packet Radio (TAPR) group was about to unveil new packet radio equipment into the amateur world — a torrent that has now placed over 1000 sets of hardware in the hands of radio amateurs around the world. But AX.25 defined just two layers of the protocol — the "physical" layer and the "link" layer. The former gives guidelines for the electrical properties of the equipment required for person-to-person packet communicating and the latter specifies the actual commands that link the communicators together in a common, though user-transparent, software bond. The goal of these standards is to establish (by radio) a virtual "wire" connection between individual users.

(Cont. on page 11)